

GLC Products

LUBE CUT™, DARK

STOCK #'S: 51001, 51005, 51055

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURED FOR: ANTI-SEIZE TECHNOLOGY
EMERGENCY TELEPHONE #: 847-455-2300
CHEMICAL FAMILY: CUTTING OIL

SECTION II - HAZARDOUS INGREDIENTS

| | CAS # | OSHA PEL, | TLV | SARA III | PROP65, | PERCENT |
|-----------------------------------|------------|-----------|---------|----------|---------|---------|
| HYDROTREATED LIGHT NAPHTHENIC OIL | 64742-53-6 | 5mg/m3 | 5mg/m3 | NO | NO | 60 - 80 |
| PARRAFFINIC DISTILLATE HEAVY | 64742-54-7 | 5mg/m3 | 5mg/m3 | NO | NO | 10 - 30 |
| DI-TERTIARY-NONYL POLYSUFIDE | 68425-16-1 | NO DATA | NO DATA | NO | NO | 1 - 10 |

SECTION III - PHYSICAL PROPERTIES

| | |
|---|---------------------------------------|
| BOILING POINT: 465 TO 465 F | SOLUBILITY IN WATER: INSOLUBLE |
| MELTING POINT: DOES NOT APPLY | REACTIVITY IN WATER: NONE |
| VAPOR PRESSURE: < 0.1 mmHG | SPECIFIC GRAVITY: 0.91 |
| EVAPORATION RATE: NIL | PERCENT VOLITILE: < 0.1% |
| APPEARANCE AND ODOR: MILD PETROLEUM ODOR | |

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT AND METHOD USED: 320 F. C.O.C.
FLAMMABLE LIMITS: LEL: 0.9 UEL: 7.0
EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES: THIS COMPOUND WILL NOT BURN UNLESS IT IS PRE-HEATED. WATER FOG MAY BE USED TO COOL THE CONTAINERS BUT DO NOT SPRAY DIRECTLY INTO LARGE CONTAINERS OF BURNING LIQUIDS AS FROTHING MAY OCCUR. WEAR A "N.I.O.S.H." APPROVED ORGANIC VAPOR RESPIRATOR.
UNUSUAL FIRE AND EXPLOSION HAZARDS: DENSE SMOKE AND NOXIOUS OR TOXIC FUMES MY BE GENERATED IN A FIRE. FIRE FIGHTERS SHOULD WEAR A SELF CONTAINED BREATHING APPARATUS

SECTION V - PHYSICAL HAZARDS

STABILITY: (X) STABLE () UNSTABLE
CONDITIONS TO AVOID: AVOID CONTACT WITH STRONG ACIDS, STRONG BASES, AND STRONG ALKALI'S
INCOMPARABILITY (MATERIALS TO AVOID): AVOID CONTACT WITH STRONG OXIDIZING AND REDUCING AGENTS.
HAZARDOUS DECOMPOSITION PRODUCTS: THE THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDANT UPON THE COMBUSTION CONDITIONS. FUMES MAY BE GENERATED, SOME OF WHICH MAY BE TOXIC OR IRRITATING. BY-PRODUCTS CAN INCLUDE HYDROGEN CHLORIDE AND OXIDES OF SULFUR.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARDS AND FIRST AID

ROUTES OF ENTRY: SKIN EYES INHALATION INGESTION

HEALTH HAZARDS: May cause temporary mild eye irritation and redness. Prolonged or repeated skin exposure may result in the loss of natural oils accompanied by dryness, cracking and dermatitis. Ingestion may result in gastrointestinal irritation, nausea, vomiting and diarrhea. Overexposure to vapors or mist may result in upper respiratory tract irritation and difficulty breathing. This product contains mineral oil for which OSHA has established an 8-hour TWA PEL of Mg/m³ as a mist. The ACGIH recommends a 15 minute stel tlv of 10 Mg/m³ for mineral oil mist.

EMERGENCY FIRST AID PROCEDURES

SKIN: WASH WITH SOAP AND WATER, USING A NAIL BRUSH. PAY PARTICULAR ATTENTION TO FINGER NAILS AND OPEN WOUNDS.

EYES: THIS PRODUCT COULD CAUSE SOME IRRITATION IF GOTTEN INTO THE EYES AND RUBBED. FLUSH EYE WITH WATER FOR 15 MINUTES, LIFTING THE EYELIDS. IF IRRITATION PERSISTS CONSULT A PHYSICIAN.

INGESTION: IF INGESTED THIS PRODUCT IS NOT EXPECTED TO CAUSE AN ACUTE REACTION. THIS PRODUCT CONTAINS A PETROLEUM OIL, DO NOT INDUCE VOMITING, BECAUSE THE OIL MAY BE ASPIRATED INTO THE LUNGS. USE A GASTRIC LAVAGE, AND CALL A POISON CONTROL CENTER OR A PHYSICIAN.

INHALATION: NOT LIKELY UNDER NORMAL CONDITIONS OF USE. IF USING IN HIGH TEMPERATURE APPLICATIONS WHERE THERMAL DECOMPOSITION IS LIKELY, USE A LOCAL EXHAUST TO REMOVE FUMES. IF DIZZINESS OR IRRITATION OCCURS, SEEK FRESH AIR.

CHEMICAL(S) LISTED AS CARCINOGENS

NPT ?: NO **I.A.R.C ?:** NO **OSHA ?:** NO

SECTION VII - SPECIAL PRECAUTION AND SPILL PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN CLOSED CONTAINERS AWAY FROM INTENSE HEAD OR OPEN FLAMES. DO NOT RE-USE OR CUT CONTAINERS.

OTHER PRECAUTIONS: DO NOT TRANSFER TO UNMARKED CONTAINERS. KEEP AWAY FROM CHILDREN. USE A SPLASH SHIELD TO MINIMIZE EXPOSURE TO MISTS.

POST SPILL/LEAKAGE PROCEDURES: DIKE THE AREA WITH ABSORBENT MATERIALS. DO NOT ALLOW THIS MATERIAL TO ENTER SEWERS OR WATERWAYS. USE AN OIL ABSORBENT MATERIAL AND DISPOSE OF PROPERLY.

WASTE DISPOSAL: DISPOSE IN A REASONABLE MANNER. FOLLOW LOCAL, STATE, AND FEDERAL GUIDELINES. DO NOT DISCHARGE INTO SEWERS OR WATERWAYS. INCINERATION IS THE PREFERRED METHOD OF DISPOSAL, ALTHOUGH IT CAN BE LANDFILLED AT AN APPROVED FACILITY.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NORMALLY NOT REQUIRED. IF THIS PRODUCT IS BEING USED IN HIGH TEMPERATURE APPLICATIONS WHERE THE PRODUCT "SMOKES", USE A LOCAL EXHAUST OR VENTILATE THE AREA TO MAINTAIN THE AIR QUALITY. A "N.I.O.S.H." APPROVED ORGANIC VAPOR RESPIRATOR IS ALSO ACCEPTABLE.

PROTECTIVE GLOVES: NORMALLY NOT REQUIRED UNLESS PROLONGED OR REPEATED SKIN CONTACT IS EXPECTED, THEN USE NEOPRENE GLOVES.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SPLASH SHIELD OR A FULL FACE MASK ARE RECOMMENDED.

WORK/HYGIENIC PRACTICES: USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT EAT OR SMOKE WHILE USING, AND THOROUGHLY WASH WITH SOAP AND WATER, USING A NAIL BRUSH AFTER USING.

ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: UNDER EPA-CWA, THIS PRODUCT IS CLASSIFIED AS AN OIL UNDER SECTION 313. SPILLS INTO OR LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER, 1-800-424-8802.

OSHA: HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD 29 CFR 1910. 1200

CERCLA-SARA HAZARD CATEGORY: NO HAZARDOUS INGREDIENTS.

SARA SECTION 313: NONE

TASCA: NONE

CANADIAN WHMIS: NO INFORMATION AVAILABLE.

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM THE USE OF THIS PRODUCT. THEREFOR, BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO LIABILITY FOR ITS USE.